

12V  
DC

Mobile

18  
GPM


69 L/min



> Fuel Transfer Pump

M-180

Series



STANDARD  
PRESSURE

IDEAL FOR USE WITH  
AUTO NOZZLE  
METER



» GPI EXCLUSIVE!

Factory-Installed  
Power Cord: Reduced  
Installation Time

Spin Collar  
Mount: Easy  
Installation  
and Pump  
Orientation

Lockable  
Nozzle Holder

Filter Kit  
Package  
Available



Class 1, Div 2  
PO = Class 1, Div 1

ELECTRICAL

Input:	12V (dc)
Type:	Rotary Gear
Current Draw:	20 amp
Motor:	2000 RPM, 1/4 HP, UL Listed to US and Canadian Standards

PERFORMANCE

Flow Rate:	18 GPM (69 L/min)
Duty Cycle:	30 min. ON, 30 min. OFF

OPERATING PRESSURE

15 psi (1.03 bar) - Standard Pressure

OPERATING TEMPERATURE

-20°F to 125°F (-29°C to 52°C)

PUMP HOUSING

Corrosion-Resistant Diecast Aluminum

MECHANICAL CONNECTIONS

Inlet / Outlet: 1 in. NPT

Mounting: 2 in. NPT

DISPENSING HOSE

12 ft. (3.7 m) x 1 in.

SUCTION PIPE

Telescoping 15 to 40 in.  
(38.1 to 101.6 cm)

POWER CORD

18 ft. (5.5 m), 12/2 AWG

WARRANTY

2 Year Pump



a M-180S-AU

Filter Kit Pkg  
Available



b M-180S-ML

Filter Kit Pkg Available

> Ordering Information

	Part No.	Model	Nozzle	Hose	Power Cord	Suction Pipe	Filter Kit
a	110300-2	M-180S-AU	Automatic	12 ft.	Installed	Included	None
b	110300-1	M-180S-ML	Manual	12 ft.	Installed	Included	None
c	110300-7	M-180S-PO	None	None	Included*	None	None
d	110612-02	M-180S-AU with filter kit	Automatic	12 ft.	Installed	Included	Included
e	110612-01	M-180S-ML with filter kit	Manual	12 ft.	Installed	Included	Included



c M-180S-PO

\*Customer installation required